

CAP320, CAPT340, CAH330

Eaton's Cooper Intelligent addressable sensors



This range of intelligent addressable sensors have been specifically designed to operate with Eaton's Cooper intelligent addressable fire systems.

All sensors are third party approved to the relevant section of EN54 (part 7 for smoke detectors & part 5 for heat detectors).

The optical sensor (CAP320) is suitable for most applications giving the fastest response to slow burning or smouldering fires which give rise to large visible smoke particles.

The photo-thermal sensor (CAPT340) will respond quickly to fast clean burning fires yet maintain the advantage of optical sensors when detecting smouldering fires. The thermal enhancement of this sensor allows a higher alarm threshold which provides a greater rejection of false alarms. The sensor will also raise an alarm at temperatures exceeding 60°C.

The CAPT340 has day/night modes available, programmeable from the site installer software. The day mode uses the heat aspect of the sensor for areas which may have smoky environments during, for example working hours. The night mode uses a combination of A2S and smoke detection. If not programmed, the sensor defaults to dual mode.

The heat sensor (CAH330) can be set to one of 3 modes 77°C / 92°C and rate of rise. These sensors are designed to be used in environments where the ambient conditions might cause false alarms if smoke detection were to be used, for example where there is a high level of dust, fumes, steam or smoke under normal conditions.

Features

- Soft addressed
- Integral short circuit isolator
- Single address
- Wide range of sensor types
- 360° visibility LED using lightpipe technology
- Drift compensation
- Aesthetically pleasing

Benefits

- Quick and simple to install
- Single "multi-mode" heat sensor
- Wide viewing angle for increased LED visibility
- Common mounting base
- Positive "lock" indication
- Discreet design for incorporation into any decor
- Easy to maintain/service

Technical Specification

| Code | CAP320 | CAPT340 | CAH330 |
|---------------------------------|---|---|---|
| Description | Optical Smoke Sensor | Photo-Thermal Sensor | Multi-Mode Heat Sensor |
| Standards | EN54 Pt7 2000 + A1:2002, EN54 Pt17 | EN54 Pt7 2000 + A1:2002, EN54 Pt17 | EN54 Pt7 2000 + A1:2002, EN54 Pt17 |
| Operating volatage | 18V dc to 30V dc | 18V dc to 30V dc | 18V dc to 30V dc |
| Standby current | 220µA (max) | 220µA (max) | 220µA (max) |
| Alarm current | 5mA (max) | 5mA (max) | 5mA (max) |
| Addressing Mode | Auto address | Auto address | Auto address |
| Specification | | | |
| Mounting position | Ceiling in open areas | Ceiling in open areas | Ceiling in open areas |
| Mounting options | Surface mount with CAB300 base | Surface mount with CAB300 base | Surface mount with CAB300 base |
| Area coverage | 100m ² (subject to local standard) | 100m ² (subject to local standard) | 100m ² (subject to local standard) |
| System wiring | Min. 1.5mm, 2 core loop or spur | Min. 1.5mm, 2 core loop or spur | Min. 1.5mm, 2 core loop or spur |
| Heat Class | | | |
| Rate of Rise | N/A | A1S | A1R |
| Fixed Heat 77°C | N/A | N/A | BS |
| Fixed Heat 90°C | N/A | N/A | CS |
| Alarm Temperature (static) | | | |
| A1R | N/A | 60°C | 60°C |
| BS | N/A | N/A | 77°C |
| CS | N/A | N/A | 90°C |
| Indication | 360° visibility light pipe | 360° visibility light pipe | 360° visibility light pipe |
| Environmental | | | |
| Operating temperature | -10°C to +60°C | -10°C to +50°C | -10°C to +60°C |
| Humidity (non condensing) | 0 to 95% RH | 0 to 95% RH | 0 to 95% RH |
| Physical | | | |
| Construction | PC/ABS | PC/ABS | PC/ABS |
| Colour - Ral No. | White - 9003 | White - 9003 | White - 9003 |
| Dimensions Excel Base (Dia x D) | 101mm x 33mm | 101mm x 43mm | 101mm x 43mm |
| Dimensions Incl Base (Dia x D) | 104mm x 45mm | 104mm x 55mm | 104mm x 55mm |
| Weight (without base) | 76g | 76g | 76g |
| IP Rating | IP30 | IP30 | IP30 |
| Compatibility | | | |
| Suitable for use with | Cooper Intelligent Addressable Fire Systems | Cooper Intelligent Addressable Fire Systems | Cooper Intelligent Addressable Fire Systems |

Dimensions

| Description | Dia (mm) | D (mm) (excl base) | D1 (mm) (incl base) |
|-----------------|----------|-----------------------|------------------------|
| Optical | 101 | 33 | 45 |
| Photo-Thermal | 101 | 43 | 55 |
| Multi-Mode Heat | 101 | 43 | 55 |

Catalogue numbers

| Description | Code |
|---------------------------------------|---------|
| Optical Smoke Sensor | CAP320 |
| Photo/Thermal Sensor | CAPT340 |
| Multi-Mode Heat Sensor | CAH330 |
| Standard Base | CAB300 |
| Conventional Remote Indicator | CIR301 |
| Duct Probe (requires detector & base) | MDP201 |
| Loop connected remote indicator | MRIAD |

